



Your Choice Expands with the RQ7 Series, Making 4K Accessible in Immersive Spaces

## PT-RQ6L

Your Choice Expands with the RQ7 Series, Making 4K Accessible in Immersive Spaces

### Key Features

Making Immersive 4K Visuals Accessible

Compact Design for an Effortless Workflow

Stable, Reliable, and Efficient Projection



PT-RQ6L

<https://eu.connect.panasonic.com/gb/en/products/projectors/pt-rq6l>

<b>Projector type</b>	1-Chip DLP™ projector
<b>DLP™ Chip</b>	
<b>Panel Size</b>	16.5 mm (0.65 in) diagonal (16:9 aspect ratio)
<b>Display Method</b>	DLP™ chip x 1, DLP™ projection system
<b>Number of Pixels</b>	2,073,600 (1920 x 1080 pixels)
<b>Light Source</b>	Laser diodes
<b>Light Output*1 *2</b>	6,500 lm
<b>Time until light output declines to 50 %*3</b>	20,000 hours (NORMAL/QUIET), 24,000 hours (ECO)
<b>Resolution</b>	4K (3840 x 2160 pixels) (Quad Pixel Drive: ON)
<b>Contrast Ratio*2</b>	15,000:1 (Full On/Full Off, Dynamic Contrast [3]) (TBD)
<b>Center-to-corner zone ratio*2</b>	90%
<b>Lens</b>	Optional (no lens included with this model)
<b>Keystone Correction Range</b>	TBD
<b>Installation</b>	Ceiling/floor, front/rear, free 360-degree installation
<b>Terminals   HDMI™ IN</b>	HDMI™ x 2 (Deep Color, compatible with HDCP 2.3, 4K/60p signal input5)
<b>Terminals   Serial In</b>	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)
<b>Terminals   Serial Out</b>	D-sub 9-pin (male) x 1 for link control (RS-232C compliant)
<b>Terminals   Remote In</b>	M3 stereo mini-jack x 1 for wired remote control
<b>Terminals   Remote Out</b>	M3 stereo mini-jack x 1 for link control (for wired remote control)
<b>Terminals   DIGITAL LINK/LAN</b>	RJ-45 x 1 for network and DIGITAL LINK connection (video/network/serial control) (HDBase™ compliant), 100Base-TX (Compatible with PLink™ [Class 2], Art-Net, HDCP 2.3, Deep Color, 4K/60p5, 6 signal input)
<b>Terminals   LAN</b>	RJ-45 x 1 for network connection, PLink™ (Class 2) compatible, 10Base-T/100Base-TX, Art-Net compatible
<b>Terminals   USB</b>	USB connector (Type A) x 1 for optional AJ-WM50 Series Wireless Module/USB memory (dual-use with DC OUT terminal)
<b>Terminals   DC Out</b>	USB Type A x 1 (for power supply, DC 5 V, 2 A)
<b>Terminals   Expansion Slot</b>	Open slot for function boards, Intel® SDM compatible
<b>Protocol versions</b>	IPv4, IPv6*7
<b>Power Supply</b>	AC 100–240 V, 50/60 Hz
<b>Maximum power consumption*8</b>	650 W (6.6–2.9A) (660 VA) (TBD)
<b>On-mode power consumption (Operating mode) *8</b>	
<b>NORMAL</b>	500 W (TBD)
<b>ECO</b>	370 W (TBD)
<b>QUIET</b>	365 W (TBD)
<b>Cabinet Materials</b>	Molded plastic
<b>Operation Noise*2</b>	35 dB (NORMAL/ECO), 32 dB (QUIET) (TBD)
<b>Dimensions (W x H x D)</b>	Approx. 498 x 170 x 440 mm (19 19/32" x 6 11/16" x 17 5/16") (With legs at shortest position, excluding lens and protruding parts) (TBD)
<b>Weight *9</b>	18.0 kg (39.7 lbs) or less (TBD)
<b>Operating Environment</b>	Operating temperature: 0–45 °C (32–113 °F)10, operating humidity: 10–80 % (no condensation)
<b>Applicable Software</b>	Multi Monitoring & Control Software, Projector Network Setup Software, Real-Time Tracking Projection-Mapping System11, Geometry Manager Pro, Smart Projector Control for iOS/Android™
<b>Control function via LAN</b>	Crestron Connected™ V2, Crestron XiO Cloud™, Art-Net DMX, AMX® DD, and PLink™ (Class 2)