

Philips Signage Solutions Collaboration Display

75" Powered by Android Multi-touch



75BDL3152E

Interactive education display

Featuring multi-touch technology

This interactive display maximises engagement and inspires collaboration with up to 40 touchpoints. Powered by Android 13 and with toughened anti-glare and anti-reflection glass, it's made to withstand heavy daily use in busy environments.

Smart and powerful

- OPS slot allows PC embedding without cabling
- Android SoC for seamless software and app integration
- PPDS Wave-ready for remote display management and control
- Built-in motion sensors

Style and safety built-in

- Cast directly from any device
- Near Field Communication (NFC) for security
- 0-gap touch frame
- Anti-glare and anti-reflection toughened glass 7 MOH
- Palm rejection
- Blue light filter

Interactive and collaborative

- Multi-touch technology capable of 40 touchpoints
- Advanced IR touch

PHILIPS

Highlights

OPS slot

Integrate a full-power PC or Android-powered CRD module directly into your Philips Professional Display. The OPS slot contains all the connections you need to run your slot-in solution, including a power supply.

Powered by Android

Our integrated Android 13 OS has been specially developed to bring a next level secure professional System on Chip. Save your favourite apps and software directly into the display or, choose from the large library of Android apps and play content from there.

PPDS Wave-ready

Your PPDS Wave-ready display enables you to manage and maintain this device remotely, wherever you are, whenever you choose. This evolutionary cloud platform puts you fully in control, with simplified installation and set-up, monitoring and controlling displays, upgrading firmware, managing central content needs, and setting power schedules. Saving you time, energy and environmental impact.

Built-in motion sensors

Built-in motion sensors contribute to energy savings by activating power-saving when no movement is detected.

0-gap touch frame

0-gap touch frame

Anti-glare and anti-reflection

Anti-glare, anti-reflection, anti-fingerprint, 7 MoH hardness.

Blue light filter to help prot

Blue light filter to help protect eyes.

Palm rejection Palm rejection for enhanced precision.

Multi-touch technology

Create a memorable interactive experience with up to 40 touchpoints at the same time for slick, agile lessons. Perfect for collaborative and competitive applications, this display connects your audience with any content. And the touch panel is HID compliant, providing true plug-and-play operation.

Advanced IR touch with smaller

Advanced IR touch with smaller, shallower bezels.

Wireless presentations

Philips ScreenShare makes it easy for teachers and students to wirelessly share their screens

from their own device, whatever the operating system, via the browser or their favourite apps, onto the Philips Interactive Collaboration display.

Cast directly from any device

Teachers and students can cast directly from their device with AirPlay, Google Cast, and Miracast.

Embedded whiteboard application

The imbedded wwhiteboard applicationn enables sseamless collaboration and brainstorming directly on the display.

Near Field Communication (NFC) for security

NFC (Near Field Communication) offers secure authentication and access control, enhancing security with encrypted data transfer. Its contactless operation minimizes the risk of unauthorized access or data interception, ensuring reliable security of the displays.

Specifications

Connectivity

- Audio output: 3.5 mm Mini Jack (x1), SPDIF
- Video input: HDMI 2.0 (x3), VGA (Analog D-Sub) (x1), USB-C (up to 65W), USB 2.0 (x1), USB 3.0
- (x4)
- Audio input: 3.5 mm mini jack (x1)
- Other connections: OPS, micro SD, USB-B (x3)
 External control: IR (in/out) 3.5 mm jack, RS232C (in/out) 2.5 mm jack, RJ45 x2

Picture/Display

- Diagonal screen size (metric): 189.3 cm
- Diagonal screen size (inch): 74.5 inch
- Aspect ratio: 16:9
- Panel resolution: 3840 x 2160
- Pixel pitch: 0.42975 (H) x 0.42975 (V)[mm]
- Optimum resolution: 3840 x 2160 @ 60 Hz
- Brightness: 350 cd/m²
- Display colors: 1.07 B
- Contrast ratio (typical): 5500:1
- Response time (typical): 6.5 ms
- Viewing angle (horizontal): 178 degree
- Viewing angle (vertical): 178 degree
 Picture enhancement: 3/2 2/2 motion pull down, 2D Combfiltor Motion company dointerlacing
- 3D Combfilter, Motion compens. deinterlacing, Progressive scan, 3D MA deinterlacing, Dynamic contrast enhancement
 Panel technology: VA
- Operating system: Android 13
- OS UI resolution: 1920 x 1080 @ 60 Hz
- Convenience

• Placement: Landscape (16/7)

- Screen saving functions: Pixel Shift, Low Brightness
- Keyboard control: Lockable
- Remote control signal: Lockable
- Signal loop through: RS232, IR Loopthrough
- · Ease of installation: AC Out
- Other convenience: Carrying handles
- Network controllable: RS232, RJ45

Sound

• Built-in speakers: 2 x16 W

Power

- Mains power: 100 ~ 240 VAC, 50/60Hz
- Consumption (Typical): 155 W
- Consumption (Max): 425 W
- Standby power consumption: <0.5W
- Power Saving Features: Smart Power
- Energy Label Class: G

Supported Display Resolution

- Computer formats: 720 x 400, 70Hz, 832 x 624, 75Hz, 1440 x 900, 60Hz, 1600 x 900, 60Hz, 1680 x 1050, 60Hz, 1920 x 1080, 60Hz, 1024 x 768, 60Hz, 1152 x 870, 75Hz, 1280 x 1024, 60Hz, 1280 x 720, 60Hz, 3840 x 2160, 30, 60Hz, 640 x 480, 60,67,75Hz, 800 x 600, 60Hz
- Video formats: 480i, 60Hz, 480p, 60Hz, 720p, 50, 60Hz, 1080i, 50, 60Hz, 1080p, 50, 60Hz, 2160p, 30, 60Hz, 576i, 50Hz, 576p, 50Hz

Dimensions

- Set Width: 1709.4 mm
- Set Height: 1020.2 mm
- Set Depth: 85.4 mm
- Set Width (inch): 67.30 inch
- Set Height (inch): 40.17 inch
- Wall Mount: 800 x 400 mm, M8
- Set Depth (inch): 3.36 inch
- Bezel width (L/R, T/B): 16.6mm (L/R/T) / 45.0mm (B)

Weight

- Product with packaging (kg): 62.5 kg
- Product with packaging (lb): 137.79 lb
- Product without stand (kg): 51.4 kg
- Product without stand (lb): 113.32 lb

Operating conditions

• Altitude: 0 ~ 5000 m

- MTBF: 30,000 hour(s)
- Temperature range (storage): -20~60 °C
- Humidity range (operation)[RH]: 10 ~ 90% (without condensation)
- Humidity range (storage) [RH]: 10 ~ 90% (without condensation)

Multimedia Applications

- USB Playback Video: H.263, H.264, H.265, MPEG1/ 2, MPEG4, VP9
- USB Playback Picture: BMP, JPEG, PNG
- USB Playback Audio: AAC, MPEG, HEAAC

Internal Player

- CPU: Quad Core Cortex A55
- GPU: Multi-Core Mali-G52
- Memory: 4GB RAM
- Storage: 32 GB eMMc
- Wifi: 2G/5G/6G 2T2R

Accessories

- Included Accessories: Cleaning cloth (x1), HDMI Cable (3m) (x1), IR sensor cable (1.8 m) (x1), Philips logo (x1), Quick start guide (x1), Remote control & AAA batteries, RS232 daisy chain cable (x1), Touch Pen (x2), USB A to B cable (3m) (x1), RS232 cable, AC Power Cord, Cable clip (x3), AC switch cover & Screw x1, DVI-D cable, USB cover and screws
- Optional accessories: Interact dongles

Miscellaneous

- On-Screen Display Languages: Arabic, Dutch, Danish, English, French, Finnish, German, Italian, Japanese, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Simplified Chinese, Turkish, Traditional Chinese
- Warranty: 5 year warranty
- Regulatory approvals: CE, FCC, Class A, RoHS, CB, EAC, EMF, ETL

75BDL3152E/00

Specifications

- Interactivity
 Multi-touch technology: 0-gap Infrared touch
 Touch points: 50 simultaneous touch points
- Plug and play: HID compliant
 Protection glass: Anti-Glare, Tempered safety glass 7MOHS



Issue date 2024-05-20 © 2024 Koninklijke Philips N.V. All Rights reserved. Version: 6.6.0

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

EAN: 87 12581 80607 1 www.philips.com