



Kindermann Displays

Touchdisplays TD-40xx

- > Capacitive touch with active stylus pen for a Surface tablet-like experience.
- > USB-C: One connector for image, sound, data, touch and 65 watts PowerDelivery.
- > No operating system - no IT security issues.
- > Optical bonding and brilliant colours for an inspiring picture in 4K.
- > Active pen with a battery life of up to 120 hours included.
- > High luminosity with low energy consumption.

Technical data

Model		TD-4065	TD-4075	TD-4086
Article number		3050000052	3050000053	3050000054
Panel	Diagonal / visible surface	65" / 1428 x 804 mm	75" / 1650 x 928 mm	86" / 1895 x 1066
	Panel type / backlight	VA / Direct LED		
	Resolution / aspect ratio / colour depth	3840 x 2160 / 16:9 / 10 bit (1.07 trillion colours)		
	Direction of use / Maximum service life (daily)	Lateral & horizontal / 18 hours		
	Brightness (typical)	~600 cd/m ²	~600 cd/m ²	~600 cd/m ²
	Contrast (dynamic)	4000:1		
	Response time (typical)	6ms		
	Frame rate	60Hz		
	Viewing angle	178°(H) / 178°(V)		
	Minimum service life	>30.000 Operating hours		
Touch	Touch technology	PCAP - capacitive touchscreen with support for active input pens		
	Distance panel / front glass	Optical-Bonding		
	Touch points	up to 10 points, incl. support for Microsoft Pen Protocol 2.0		
	Front glass	Tempered glass, 3 mm thick, MoHS7, anti-reflective, highly transparent		
	Transmission / Haze-Level	> 80% / < 12%		
	Minimum object size / Precision	Finger < 2.5 mm, active pin < 2 mm		
	Active pen (Windows)	Pen tip: mouse, writing, marking, etc. Back: erasing		
	Driver	Plug and Play (HID)		
	Operation	Finger, passive tablet stylus (> 8mm), active stylus		
	Single touch compatibility	Windows 10/11, Android, ChromeOS, MacOS X (driver required)		
	Single touch	Linux, MacOS X (driver required)		
	Battery (active pen)	65 mAh lithium battery for 120 hours of continuous use, charged in 40 minutes via USB-C		
	Loudspeaker	Configuration / power	2.1 system with 20W each - Frequency response: 80 - 20,000 Hz	
Menu	Languages	German, English, French, Italian		
	Public-USB	3x USB 3.0 type A		
Connections Front (lateral)	HDMI 2.0 input	1		
	USB Typ C input	1x with support for video (3840x2160@60Hz DP Alt Mode), touch, data transfer, USB PD 3.0 max. 20V / 3.25 A (65 Watt)		
	Touch-USB	1x USB 3.x type B		
	Sensors	Ambient light sensor		
Connections Rear (top)	Camera connection (Public-USB)	1x USB-C 3.x (data only)		

Model		TD-4065	TD-4075	TD-4086
Connections lateral	OPS slot	1x JAE 80pin (power supply 12 - 19V /2.5/5A)		
	Touch-USB	1x USB 2.0 type B		
	HDMI 2.0 input	1		
	VGA / Audio (3.5 mm jack) input	1 / 1 (1920x1080@60Hz)		
	Public-USB	2x USB 2.0 type A (1x at the bottom)		
	HDMI output	1 (below)		
	Audio output (3.5 mm jack)	1 (below)		
	Mic-In (3.5 mm jack)	1		
	LAN	2x RJ45 100/1000 MBit/s		
	RS232	1 (9pin SubD (bottom))		
Power connection	Input voltage / connection	100 V ~ 240 V/AC, 50/60 Hz - IEC socket		
	Consumption (typical)	approx. 137 W	approx. 175 W	approx. 213 W
	Consumption (eco)	approx. 97 W	approx. 113 W	approx. 130 W
	Standby consumption	<0.5W		
Environmental conditions	Temperature - operation	0 - 40°C		
	Temperature - storage	-20 - 60°C		
	Humidity - operation	10 - 90% (non-condensing)		
	Humidity - storage	10 - 90% (non-condensing)		
Dimensions / Material	Display dimensions (mm) (WxDxH)	1485 x 81 x 869	1707 x 82 x 994	1953 x 81 x 1133
	Packing dimensions (mm) (WxDxH)	1690 x 210 x 1060	1920 x 210 x 1150	2140 x 216 x 1347
	Net weight approx. (kg)	42	57	70
	Gross weight approx. (kg)	56	72	89
	Housing	Aluminium/metal		
	Frame width (top/bottom/left/right)	1,5 mm (all sides)		
	VESA	4 x M8 500 x 400 mm	4 x M8 600 x 400 mm	4 x M8 800 x 400 mm
Accessories	Scope of delivery	IR remote control, mains cable (3 m), USB A/B cable (3 m), HDMI cable (3 m), 1x active control pen incl. USB A/C charging cable, Quickstart Guide		

Subject to change - Status 12/08/2024

All prices are net prices excl. VAT.
Subject to change in the interest of progress. Illustrations and technical specifications may contain additional options and are not binding for the design. All dimensions are subject to the usual tolerances.



Kindermann GmbH
Mainparkring 3 | D-97246 Eibelstadt | Germany
Phone +49 9303 9840-0 | Email: info@kindermann.de
Printed in Germany | 11/2024

www.kindermann.com

Presented by:

