



### Kindermann displays

# Touchdisplays TD-11<sup>2</sup>

- > Future-proof: High-performance processor, WiFi6 and 2x USB-C inputs
- > USB-C one for all: video, sound, data, touch and 65 watts charging current at the same time
- > Android 13
- > Intuitive user interface, designed in Germany
- > Screensharing via hardware dongle, app, AirPlay & Chromecast
- > 40 touch points

# Technical data

Model		TD-1155 <sup>2</sup>	TD-1165 <sup>2</sup>	TD-1175 <sup>2</sup>	TD-1186 <sup>2</sup>
Article number		3050000061	3050000062	3050000063	3050000064
Panel	Diagonal / visible surface	55" / 1428 x 804 mm	65" / 1428 x 804 mm	75" / 1647 x 927 mm	86" / 1895 x 1066
	Panel type / backlight	IPS / Direct LED			
	Resolution / aspect ratio / colour depth	3840 x 2160 / 16:9 / 10 bit (1.07 billion colours)			
	Direction of use / Maximum service life (daily)	Landscape / 18 hours			
	Brightness (typical)	>350cd/m <sup>2</sup> (typ.)	>350cd/m <sup>2</sup> (typ.)	>400cd/m <sup>2</sup> (typ.)	>400cd/m <sup>2</sup> (typ.)
	Contrast (dynamic)	5000:1			
	Response time (typical)	8ms			
	Frame rate	60Hz			
	Viewing angle	178°(H) / 178°(V)			
	Minimum service life	50.000 operating hours			
Touch	Touch technology	Infrared, with high precision			
	Distance panel / front glass	2 mm	Zero-/Direct-bonding		
	Touch points	up to 40 points, incl. support for Microsoft Windows 10/11 pen protocol 2.0			
	Front glass	Tempered glass, thickness 3.2 mm, MoHS7, anti-glare, highly transparent			
	Transmission	>92%			
	Minimum object size / Precision	1,6 mm / ±1 mm			
	Minimum touch height	1,2 mm			
	Tool recognition	Fine pencil: <3 mm, thick pencil: <8 mm, small eraser: >12 mm, thick eraser: > 25 mm			
	Driver	Plug and Play (HID)			
	Operation	Finger, operating pen with round tip or comparable objects			
Multitouch compatibility	Windows 10/11, Android, ChromeOS, MacOS X (driver required)				
	Linux, MacOS X				
Loudspeaker	Configuration / power	Stereo sound system, 2x 20W, frequency response: 200 - 20.000 Hz			
	SoC	A311D2 OctaCore, 4x A73 @ 2,2 Ghz / 4x A53 @ 2 GHz , MaliG52 MP8			
SoC	RAM / eMMC	8 GB / 64 GB			
	WiFi	WiFi 6 - 802.11 a/b/g/n/ac/ax - Dual Band 2.4 / 5GHz, 2x2 MiMo			
	Bluetooth	5.0			
Supplied software (Android)	OS	Android 13			
	Basic functions	Kindermann Whiteboard App with annotation function and erase by gesture, screenshots, calculator, spotlight, timer and screen recorder			
	File manager	Yes, including photo, video, audio player			
	Office / PDF viewer	WPS Office, Adobe Reader			
	Browser	Firefox & Chromium			
	BYOD Wireless streaming	Yes, Eshare incl. support for HDMI and USB-C dongle, AirPlay and Chromecast (Miracast in Wifi Direct Mode)			
Menu languages	Additional apps	OpenCamera, OpenStreetmaps, Wikipedia			
	Available	German, English, French, Italian, Spanish, Dutch, Finnish, Swedish, Danish, Norwegian, Croatian, Estonian, Latvian, Lithuanian and others			

Model		TD-1155 <sup>2</sup>	TD-1165 <sup>2</sup>	TD-1175 <sup>2</sup>	TD-1186 <sup>2</sup>
Connector front side	Public-USB (Android & Windows)	2x USB 3.0 type A			
	HDMI 2.0 input	1			
	USB type C input	1x with support for video (3840x2160@60Hz DP Alt Mode), touch, data transmission, USB PD 3.0 max. 20V / 3,25 A (65 Watt)			
	Touch-USB	1x USB 3.0 type B			
	Sensors	Ambient light sensor			
Connector lateral	OPS slot	1x JAE 80-pin (power supply 18V / 5A)			
	Touch-USB	3x USB 3.0 type B			
	USB type C input	1x with support for video (3840x2160@60Hz DP Alt Mode), touch, USB PD 3.0 max. 15 Watt			
	DisplayPort 1.2a input	1			
	HDMI 2.0 inputs	2			
	VGA / Audio (3,5 mm jack) input	1 / 1 (bottom) (1920x1080@60Hz)			
	Android-USB	2x USB 3.0 type A			
	HDMI output	1 (bottom)			
	Audio output (3,5 mm jack)	1 (bottom)			
	Audio output (SPDIF, optical)	1 (bottom)			
	Mic-in	1 (bottom)			
	LAN	2x RJ45 100/1000 Mbps (bottom)			
	RS232	1 (9-pin SubD (bottom))			
	Service USB connection	1x USB 2.0 type A (for FW updates)			
	Power connection	Input voltage / connection	100 V ~ 240 V/AC, 50/60 Hz - cold-device socket		
Consumption (typical)		~120 W	~150 W	~200 W	~270 W
Consumption (eco)		~75 W	~94 W	~116 W	~175 W
Standby consumption		<0.5W			
Environmental conditions	Temperature - operation	0 - 40°C			
	Temperature - storage	-10 - 60°C			
	Humidity - operation	20 - 80% (non condensing)			
	Humidity - storage	10 - 60% (non condensing)			
Dimensions / Material	Display dimensions (mm) (WxDxH)	1299 x 93 x 792	1512 x 88 x 921	1723 x 87 x 1035	1968 x 88 x 1173
	Packing dimensions (mm) (WxDxH)	1420 x 245 x 920	1660 x 220 x 1010	1900 x 225 x 1160	2160 x 225 x 1310
	Net weight approx. (kg)	27	38	50	63
	Gross weight approx. (kg)	38	49	62	79
	Housing	Aluminum/metal			
	Frame width (top/bottom/left/right)	21/52/21/21 mm			
	VESA	4 x M6 400 x 400 mm	4 x M6 600 x 400 mm	4 x M8 800 x 400 mm	4 x M8 800 x 600 mm
Accessories	Scope of delivery	IR remote control, power cable (3 m), USB A/B cable (3 m), HDMI cable (3 m), 2x passive pens (suitable for left- and right-handers), Eraser, QuickStartGuide			

Subject to change - Status 01.2024

All prices are net prices excl. VAT.  
Subject to change in the interest of progress. Illustrations and technical specifications may contain additional options and are not binding for the design. All dimensions are subject to the usual tolerances.



**Kindermann GmbH**  
Mainparkring 3 | 97246 Eibelstadt | Germany  
Tel. +49 9303 9840-0 | Fax +49 9303 9840-101  
Printed in Germany | 01/2024

[www.kindermann.com](http://www.kindermann.com)

Presented by:

