

V6 Transcend Series

The MAXHUB V6 T Series delivers a sense of Luxury with its modern workspace aesthetic and 95% screen-to-body ratio. The all-in-one display integrates camera, microphone, speaker, and touch panel. You can start the meeting right after plugging in the power supply.



4K


Premium 4K Display

95% Screen Ratio
Wide Color Gamut , NTSC 90%
High Color Accuracy , $\Delta E \leq 2$




Touch Screen

PCAP Touch
20 Touch Points



Wireless Screen Sharing

Share your screen through
MAXHUB Share App




Built-in Camera

Dual Camera (48MP + 8MP)
3x Optical Zoom
Flippable design




Built-in Microphone

8 meters of voice pick-up
8 mic array , clear conversation



Built-in Microphone

2.2 Channel
2 x 10W + 2 x 15W



10th Gen Intel CPU

Powerful performance, fluid experience
* With use of MT61 PC Module



Smart Whiteboard

OCR supported,
Multiple built-in templates

Display

Model	T6530	T8630
Diagonal Size(inch)	65	86
Backlight	Direct-lit LED	Direct-lit LED
Panel Technology	VA	VA
Aspect Ratio	16 : 9	16 : 9
Resolution	3840 x 2160	3840 x 2160
Refresh Rate	60Hz	60Hz
Response Time	6.5ms	8ms
Brightness (typ)	350cd/m ²	350cd/m ²
Contrast Ratio	5000 : 1	4000 : 1
Viewing Angle	178°/178°	178°/178°
Color Gamut (typ)	90% NTSC	90% NTSC
Display Orientation	Landscape	Landscape
Operating Hour	16/7	16/7

Touch System

Touch Sensor	PCAP
Accuracy	± 1.5mm
Max Touch Points Supported	20
Glass	Zero Parallax , Anti-glare, Antibacterial
Supported Operating System (Touch Return)	Windows10/Windows8/Windows7/WindowsXP/ Android/Linux/Mac OS X/Chrome OS

Connectivity

Input	HDMI In x1 , USB 2.0 x1 , TOUCH 2.0 x1 ,USB Type-C x1
Audio	Audio out*1
Control	RS232*1
PC Module Slot	Yes , 3840x2160@60fps
PC Module Compatible	MT61
Wi-Fi Module	SI06

Camera&Audio&Microphone

Built-in Camera	Yes , Dual Camera 48MP (fixed lens)+8MP (with 3x optical zoom), Flippable
Camera Features	Auto frame / Speaker Tracking
Speaker Output Power	2.2 channel , 2 x 10W+2 x 15W
Microphone Array	8*far-field , beam-forming - max 8m range

Environment

Operating Temperature	-20° C~60° C
Storage Temperature	10%~90%RH
Operating Humidity	10%~90%
Storage Humidity	10%~90%

Dimension&Weight

Product Dimensions (W x H x D)	1455 x 888 x 78 mm 57.28 x 34.96 x 3.07 inch	1921 x 1151 x 78 mm 75.63 x 45.31 x 3.07 inch
shipping Dimensions (W x H x D)	1628 x 992 x 208 mm 64.09 x 39.06 x 8.19 inch	2112 x 1283 x 280 mm 83.15 x 50.51 x 11.02 inch
Net Weight (kg/pounds)	39.8 kg / 87.7 pounds	59.6 kg / 131.4 pounds
Gross Weight (kg/pounds)	51 kg / 112.4 pounds	79 kg / 174.2 pounds
Wall Mount (VESA)	600 x 400 mm / 23.62 x 15.75inch	600 x 400 mm / 23.62 x 15.75inch
Screws for VESA	M8 x 25 mm / M8 x 0.99inch	M8 x 25 mm / M8 x 0.99inch

POWER

Power Supply	AC100-240V,50/60Hz	AC100-240V,50/60Hz
Max Power Consumption	350W	500W
Standby	≤0.5W	≤0.5W

What's In The Box

Standard Power Cord, 1 x Wi-Fi Module, 2 x Passive Stylus, 1 x Wall Mount, 1 x Type-C Cable (1.8m | 70.9inch),
1 x HDMI Cable (1.5m | 59.06 inch)

Optional (Mobile Stand)



ST41B



ST23C



EST09



EST11