

# MAXHUB Touch Controller

## Model: TCP10M

Transform your meeting spaces with the MAXHUB TCP10M touch controller, designed to seamlessly control MAXHUB IFP/Commercial Display/VideoBar family with leading video conferencing solutions. With one-touch join and easy content sharing, you can enhance collaboration and elevate your meeting experience. Plus, with a simple setup using a single cable routed through the back of the device, installation is a breeze.




### High Resolution

10.1" 1920(H)×1080(V)



### Touch Screen

10-point capacitive touch recognition



### Power Over Ethernet

A single cable carries both power and data to reduce clutter




### Cable Free Paring

Connect to your Maxhub Display /VideoBar wirelessly



### Sleek Design

Control options are clear and accessible



### Compatibility

Compatible with MAXHUB IFP/Commercial Display/VideoBar S10Pro/S15 family



**Display**

|                             |                      |
|-----------------------------|----------------------|
| Size                        | 10.1 inch            |
| Resolution                  | 1920 (H) x 1080 (V)  |
| Refreshing Frequency        | 60Hz                 |
| NTSC                        | 55%                  |
| Back Light Unit             | ELED                 |
| Brightness with glass (typ) | 280cd/m <sup>2</sup> |
| Life Span                   | 15000 Hours          |

**Operating System**

|                |              |
|----------------|--------------|
| System Version | Android 10.0 |
| RAM            | 4G           |
| ROM            | 16G          |
| CPU            | A53×4        |
| GPU            | Mali-G52     |

**Touch System**

|              |  |
|--------------|--|
| Sensing Type | Capacitive touch recognition           |
| Touch Tool   | Finger,Passive infrared pen (Optional) |
| Accuracy     | ±2mm                                   |
| Touch Point  | 10 points touch                        |
| Minimum Size | 6mm                                    |

**Microphone (For pairing with host only)**

|          |      |
|----------|------|
| Quantity | 2    |
| Distance | 0~4m |

**Bluetooth**

|                   |        |
|-------------------|--------|
| Version           | 5.0    |
| Working Frequency | 2.4GHz |
| Working Distance  | 0~10m  |

**Wi-Fi**

|                   |                  |
|-------------------|------------------|
| Version           | 802.11a/b/g/n/ac |
| Working Frequency | 2.4GHz;5GHz      |
| Working Distance  | 0~10m            |

**Power**

|                     |                                |
|---------------------|--------------------------------|
| Power Requirements  | 12V3A(Adapter) / 48V0.53A(POE) |
| Overall Power(Max.) | 24W                            |
| Standby Power       | ≤0.5W                          |

**I/O Port**

|          |   |
|----------|---|
| USB 2.0  | 1 |
| RJ45 IN  | 1 |
| RJ45 OUT | 1 |
| DC2.0    | 1 |

**Physical Specifications**

|                           |                    |
|---------------------------|--------------------|
| Dimension L×H×D           | 241.6×157.4×83.2mm |
| Dimension (package) L×W×H | 320×225×145mm      |
| Net Weight                | 0.85kg             |
| Gross Weight              | 1.86kg             |

**Speaker**

|         |        |
|---------|--------|
| Channel | 1.0    |
| Power   | 1x0.8W |

**Accessories (included in the package)**

|                  |
|------------------|
| RJ45 cable (5m)  |
| Adapter (12V/3A) |

**Environmental Conditions**

|                       |                   |
|-----------------------|-------------------|
| Operation Temperature | 0℃~40℃            |
| Operation Humidity    | 10%~90%RH         |
| Storage Temperature   | -20℃~60℃          |
| Storage Humidity      | 10%~90%RH         |
| Altitude              | Below 5000 meters |

**Statement**

Size and weight vary by configuration and manufacturing process, please refer to the actual product. The product images are for illustrative purposes only and may slightly differ in appearance, colour, size, etc. from the actual product. The description, illustrations, etc. in this document may subject to change in accordance with the latest product specification and performance. Should the above-mentioned change in the document become necessary, the document may be updated without written notice.