MAXHUB

Commercial Display

Model Name: ND55CMA

Taking simplicity, safety and flexibility to new levels. MAXHUB Commercial Display makes every organization more effective and productive.





Professional 4K Display

4K Resolution Anti-Glare, 25% Haze



Wireless Screen Sharing

Share your screen through MAXHUB
Share app or wireless dongle



External Control

Display Control through IP or RS232 protocol



Device Management

Manage through cloud based MAXHUB Pivot



Built-in Speakers

2 × 16W Dual speakers



Conformal Coating

Commercial level design of hareware



Energy Saving

ErP Certified
Energy Star 8.0 Certified

Display	
Screen Size (class)	55"
Diagonal	54.6" 138.7cm
Panel Type	VA
Haze	25% (Anti-Glare)
Aspect Ratio	16:9
Native Resolution	3840 × 2160
Refresh Rate	60Hz
Brightness (Typ.)	500 nits
Backlight Type	DLED
Contrast Ratio	5,000:1 (Typ) 1,000,000:1 (Dynamic)
Viewing Angle (H × V)	178°
Response Time	6.5ms
Life Time (Min.)	≥50,000 hours
Operation Hours (Hours / Day)	24 / 7
Orientation	Portrait / Landscape

Internal Player	
Processor	A55 × 4
Graphic	Mali-G52 × 2
Memory	4G
Storage	32G
Operating System	MAXHUB Signage OS
UI Resolution	4K

Connectivity		
Input	HDMI IN × 2	2.1, 3840 × 2160 @60Hz, CEC, HDMI 1 support ARC
	USB 2.0 × 1	For system upgrades
	USB 3.0 × 1	For external peripherals
	USB Type-C × 1	Video, Audio, PD 65W,
		LAN Network Sharing Baud
	RS232 × 1	rate 9600
	RJ45 IN × 1	10M / 100M / 1000Mbps
Output	HDMI OUT × 1	Up to 4K@60Hz, Follow HDMI IN and Type-C channel Android channel do not support
	AUDIO OUT × 1	3.5mm Phone Jack
	SPDIF × 1	PCM output format
OPS Slot		No
Wi-Fi Slot		Module slot × 1
Wi-Fi		Wi-Fi 6 supported 802.11ac/b/g/n/a/ax, 2.4GHz/5GHz
Bluetooth		5.2

Environmental Conditions	
Operation Temperature	0°C ~ 40°C
Operation Humidity	10% ~ 90%RH
Storage Temperature	-20°C ~ 60°C
Storage Humidity	10% ~ 90%RH

Mechanical Specification	
Bezel Width (L × R × T × B)	9.9 / 9.9 / 9.9 / 9.9 mm 0.39 / 0.39 / 0.39 / 0.39 inch
Product Dimension (W× H × D)	1233 × 703.5 × 71.4 mm 48.54 × 27.7 × 2.81 inch
Package Dimension (W × H × D)	1332 × 819 × 156 mm 52.44 × 32.24 × 6.14 inch
Product Weight (Net)	13.40 kg / 29.54 pounds
Package Weight (Gross)	19.5 kg / 43 pounds
VESA Mount (mm)	400 × 200
Handle	No
Power	
Power Supply	100-240V~50/60Hz
Power Consumption (Standby mode)	0.5W
Power Consumption (Typical)	112.5W

Speaker Power(Max.)	2 × 16W
Certification	
Safety	IEC 62368-1
EMC	Class B

Yes

Energy Star	Yes
Feature	
Screen Share	MAXHUB Share / Miracast / AirPlay / Chromecast
Device Management	MAXHUB Pivot
Protocol Control	RS232 / IP control
Special Features	Auto signal change / Built-in media player /

Accessory			
Included in the pac	kage	Power Cord × 1 HDMI Cable × 1 Wi-Fi Module × 1 Remote Control × 1 Wall Mount × 1	
Optional	Wireless Dongle (WT13)	Mobile Stand (ST41B)	Mobile Stand (ST23C)

Warranty	
Display	years warranty



Sound

ErP

Channel memory / Auto-rotate screen