MAXHUB 01

Commercial Display

Model Name: ND65CMA

Taking simplicity, safety and flexibility to new levels. MAXHUB Commercial Display makes every organization more effective and productive.





Professional 4K Display

4K Resolution Anti-Glare, 25% Haze



Wireless Screen Sharing

Share your screen through MAXHUB
Share app or wireless dongle



External Control

Display Control through IP or RS232 protocol




Device Management

Manage through cloud based MAXHUB Pivot



Built-in Speakers

2 × 10W Dual speakers



Upgrade Your Display

OPS slot availability to transform your display into a windows-based display



Conformal Coating

Commercial level design of hareware



Energy Saving

ErP Certified
Energy Star 8.0 Certified

Display	
Screen Size (class)	65"
Diagonal	64.5" 163.9cm
Panel Type	ADS
Haze	25% (Anti-Glare)
Aspect Ratio	16:9
Native Resolution	3840 × 2160
Refresh Rate	60Hz
Brightness (Typ.)	500 nits
Backlight Type	DLED
Contrast Ratio	1,200:1 (Typ) 1,000,000:1 (Dynamic)
Viewing Angle (H × V)	178°
Response Time	8ms
Life Time (Min.)	≥50,000 hours
Operation Hours (Hours / Day)	18 / 7
Orientation	Portrait / Landscape

Internal Player	
Processor	A55 × 4
Graphic	Mali-G52 × 2
Memory	4G
Storage	32G
Operating System	Android 11.0
UI Resolution	4K

Connectivity	
Input	HDMI IN 2.0 × 3 USB Type-C × 1 (PD 65W) USB Type-A 3.0 × 1 (for external peripherals) USB Type-A 2.0 × 1 (only for firmware upgrade) RJ45 IN × 1
Output	HDMI OUT 2.0 × 1 SPDIF × 1 (Optical) RJ45 OUT × 1 AUDIO OUT × 1 (3.5mini jack)
External Control	RS232 × 1 / IR Receiver
Wi-Fi	Removable Wi-Fi Module Wi-Fi 6 Support 2.4GHz & 5GHz 802.11ac/b/g/n/a/ax
OPS Slot	Yes, 80pin

Mechanical Specification	
Bezel Width (L × R × T × B)	15.9 / 15.9 / 15.9 / 15.9 mm 0.63 / 0.63 / 0.63 / 0.63 inch
Product Dimension (W × H × D)	1463.3 × 838.3 × 76.4 mm 57.61 × 33.0 × 3.0 inch
Package Dimension (W × H × D)	1628 × 942 × 208 mm 64.09 × 37.09 × 8.19 inch
Product Weight (Net)	25.40 kg / 56.0 pounds
Package Weight (Gross)	33.25 kg / 73.30 pounds
VESA Mount (mm)	600 × 400
Handle	Yes

Environmental Conditions	
Operation Temperature	0°C ~ 40°C
Operation Humidity	10% ~ 90%RH
Storage Temperature	-20°C ~ 60°C
Storage Humidity	10% ~ 90%RH
Power	
Power Supply	100-240V~50/60Hz
Power Consumption (Typical)	165W
Power Consumption (Max)	335W
Sound	
Speaker Power Output	2 × 10W
Certification	
Safety	IEC 62368-1
EMC	Class B
ErP	Yes
Energy Star	Yes
Features	
Built-In Media Player	Yes

Screen Share			MAXHUB Share	
Accessory				
Included in th	ie package		Power Cord × 1 HDMI Cable × 1 Wi-Fi Module × 1 Remote Control × 1 Wall Mount × 1	
Optional	OPS (OPS62A)	Wireless Dongle (WT13)	Mobile Stand (ST41B)	Mobile Stand (ST23C)

MAXHUB Pivot

Device Management System

Warranty	
Display	3 years warranty







