

## INLINE® HDMI AOC KABEL, ULTRA HIGH SPEED HDMI KABEL, 8K4K, SCHWARZ



- Ultra HDMI 2.1 AOC Anschlusskabel
- Hybrid Kabel bestehend aus 4 Glasfaser- und 7 Vollkupferlitzen
- Richtungsgebundenes Signalkabel: HDMI Stecker (Quelle) an HDMI Stecker (Display)
- Robuste Metallstecker, Aramid-geschütztes und TPU-ummanteltes Kabel, schwarz
- Max. Daten Bandbreite: 48 Gb/s (12 Gb/s pro Kanal)

- Unterstützte Auflösungen: UHD-II 7680x4320/8K@60Hz - UHD-I 3840x2160/4K@120Hz
- Unterstützt 3D, HDCP, EDID, CEC, DDC, Dynamic HDR, eARC, ARC und weitere Spezifikationen gemäß HDMI
- Vergoldete Kontakte
- Kabeldurchmesser nur 4.8mm
- Betriebstemperatur: 0°C bis +50°C
- Lagertemperatur: -20°C bis +70°C

Art. Nr.	Länge	EAN
17910I	10	4043718293537
17915I	15	4043718293544
17920I	20	4043718293551
17925I	25	4043718293568
17930I	30	4043718293575
17940I	40	4043718293582
17950I	50	4043718293599

NOTE:

1. Supports resolutions to 8K@60Hz, 4K@120Hz (HDMI 2.1 standard)
2. Compatible with HDMI 2.0 standard (Supports 4K@60Hz 4K@30Hz)
3. Support 3D/HDCP2.2/EDID/HDR/eARC/ARC
4. Plug and Play
5. Hybrid optical cable with fiber and copper wire
6. Round cable Black PVC jacket OD:5.0±2.0mm
7. Raw cable Spec: (50/125um FIBER\*4C+MID)\*1+(1P\*30#+D+AL)\*1+3C\*30#+2C\*26#+F+D+AL
8. Operation temperature : 0°C→+50°C  
Storage temperature : -20°C→+70°C
9. ROHS 2.0 and REACH compliant
10. Cable Printing: Ultra High Speed HDMI™ Hybrid Fiber Optic Cable

