newline

**OPTICAL** BONDING









Superior Touch



Connectivity



Diverse



Crystalclear lmage Quality



Maximum Viewing Angle



Object Recognition



Bonded



**Bring Your** Own Device

## THE UNMATCHED POWERFUL PCAP SOLUTION

NAOS is Newline's all-new premium solution for the corporate workspace. This full range is based on the combination of optical bonding technology together with capacitive touch technology and available in different sub ranges. The primary NAOS product line is designed for unified communications and collaboration. Built in cameras, microphone array and soundbar make this product line a true all-in-one solution. Combined with Newline OPS and Newline Launch Control, you can start a video call in just seconds. Simply connect your mobile device via bluetooth low energy or scan the QR code and select your meeting from your Windows calendar.

Newline NAOS includes interactive ecosystem tools for Android and is compatible with the optional tools for Windows:



BROADCAST

DISPLAY MANAGEMENT



LAUNCH CONTROL

MODEL	TT-6520UP	TT-7520UP	TT-8620UP	
Display				
Active Screen Size	65"	75"	86"	
	05	LED (WCG + anti blue light)	00	
Backlight type				
Aspect ratio		16:9		
Resolution	3840 x 2160			
Display color	1,07 billion			
Brightness	≥400 cd/m²			
Contrast Ratio (Dynamic)	4000:1			
Viewing angle	178°			
Life Time		≥50.000 hours		
Electrical				
Power Consumption (Normal)	≤250W	≤300W	≤400W	
Power Consumption (Standby mode)		<0,5W		
Working Voltage		AC100-240V, 50/60Hz, Max 3.0A		
Touch				
Surface treatment	Optical Bo	onding / Anti-glare tempered glass + Ant	ti-fingerprint	
Touch type	Projective Capacitive Touch (P-cap)			
Writing pen	Fine passive pen			
Touch points	Windows 20 points, Android 10 points			
Speaker		тине до рожно, памена не решие		
opeane.	No speakers Built in. Please, refer to Sound bar specs			
Transportation/Storage			·	
Outline Dimension	1509 x 865 x 86 mm	1731 x 1010 x 86 mm	1977 x 1150 x 86 mm	
Package size	1640 x 1036 x 221 mm	1859 x 1160 x 247 mm	2119 x 1281 x 275 mm	
Net weight	36 Kg	49,5 Kg	57,5 Kg	
Gross weight	50,5 Kg	69 Kg	80 Kg	
VESA mount	600 x 400 mm	800 x 400 mm	800 x 400 mm	
IO Ports	355 X 155 11111	200 X 100 111111	000 X 100 111111	
	USB-A 2.0 (Android) x 1, USB-A 3.0 (Dy	namic) x 2, HDMI 2.0 (4K@60Hz) x 2, VG	GA (2K@60Hz) x 1, Audio In x 1, USB-A 3.0	
Rear input ports	(Touch) x 1, RJ45 ln x 1, RS232 x 1, Microphone ln x 1, USB-C (Sound Bar) x 1, USB-C x 1			
Rear output ports	HDMI 2.0 out (4k@60 Hz) x 1, Earphone x 1, SPDIF x 1			
OPS port	Yes, 4K@60 Hz/30 Hz			
Smart System				
CPU	A73 x 2 + A53 x 2 ( A53 : 1.05-1.3GHz; A73 : 1.15-1.5GHz)			
GPU	MaliG51 x 4			
RAM	4 GB			
ROM	64 GB			
Android version	8.0			
Wi-Fi module	Built-in 2.4G/5G, Support Wi-Fi and hotspot enable in the same time			
Built in Camera & Microphones				
Resolution Max.		1920 x 1080		
Viewing angle	900			
Built-in Microphone	Microphone array 4, Pickup distance 8m, Echo cancellation, Beamforming, Noise reduction			
Sound Bar	Whorophone array 4, Flor	Librarios ori, Eorio Gariochation, Dea	g, Holde reduction	
Speaker Position		Forward		
•	Forward 8Ω			
Speaker Rated Impedance	2 x 25W			
Speaker Max. power Output	2 x 25w 3840 x 2160			
Resolution Max.				
Viewing angle		90°		
Others				
OPS PC		Available		
Firmware update		OTA		

## newline

ASIA PACIFIC OFFICE

17F. No. 653, Banan Rd., Zhonge Dist., New Taipei City 235, Taiwan

TEL: +886 282282089

EUROPE OFFICE

Ronda de Poniente 16, Bajo E-28760, Tres Cantos,

Madrid, Spain

TEL: +34 911169178

INDIA OFFICE

Room No. 203, No.37, TTK Road, 101 East Park Blvd.

Alwarpet, Chennai, Tamil Nadu, India, 600018

TEL: +91 44 46945513

NEWLINE INTERACTIVE INC.

101 East Park Blvd Suite 807 Plano, TX 75074, USA

TEL: +1 888 233 0868