


O365 – EsignageDataConnector Einrichten

Inhalt

O365 – EsignageDataConnector Einrichten	1
1. App registrieren	2
2. Rechte erteilen	3
3. Client Secret erstellen	6
4. Werte in ESignage Data Connector eintragen	7

1. App registrieren

URL: <https://portal.azure.com>



Home > Umdasch Digital Retail GmbH

Register an application

* Name

The user-facing display name for this application (this can be changed later).

Supported account types

Who can use this application or access this API?

Accounts in this organizational directory only (Umdasch Digital Retail GmbH only - Single tenant)

Accounts in any organizational directory (Any Azure AD directory - Multitenant)

Accounts in any organizational directory (Any Azure AD directory - Multitenant) and personal Microsoft accounts (e.g. Skype, Xbox)

Personal Microsoft accounts only

[Help me choose...](#)

Redirect URI (optional)

We'll return the authentication response to this URI after successfully authenticating the user. Providing this now is optional and it can be changed later, but a value is required for most authentication scenarios.

Web

Register an app you're working on here. Integrate gallery apps and other apps from outside your organization by adding from [Enterprise applications](#).

By proceeding, you agree to the [Microsoft Platform Policies](#)

2. Rechte erteilen

ESignageDataConnector | API permissions

Search (Ctrl+/) Refresh Got feedback?

You are editing permission(s) to your application, users will have to consent even if they've already done so previously.

The "Admin consent required" column shows the default value for an organization. However, user consent can be customized per permission, user, or app. This column may not reflect the value in your o

Configured permissions

Applications are authorized to call APIs when they are granted permissions by users/admins as part of the consent process. The list of configured permissions should include all the permissions the application needs. [Learn more about permissions and consent](#)

+ Add a permission Grant admin consent for [Umdasch Digital Retail GmbH](#)

API / Permissions name	Type	Description	Admin consent req...	Status
Microsoft Graph (3)				
Calendars.Read	Application	Read calendars in all mailboxes	Yes	Granted for Umdasch Di... ...
Place.Read.All	Application	Read all company places	Yes	Granted for Umdasch Di... ...
User.Read.All	Application	Read all users' full profiles	Yes	Granted for Umdasch Di... ...

Other permissions granted for Umdasch Digital Retail GmbH


These permissions have been granted for Umdasch Digital Retail GmbH but aren't in the configured permissions list. If your application requires these permissions, you should consider adding them to the configured permissions list. [Learn more](#)

Request API permissions

Select an API


Microsoft APIs APIs my organization uses My APIs

Commonly used Microsoft APIs




Microsoft Graph

Take advantage of the tremendous amount of data in Office 365, Enterprise Mobility + Security, and Windows 10. Access Azure AD, Excel, Intune, Outlook/Exchange, OneDrive, OneNote, SharePoint, Planner, and more through a single endpoint.




Azure DevOps

Integrate with Azure DevOps and Azure DevOps server



Azure Rights Management Services

Allow validated users to read and write protected content



Azure Service Management

Programmatic access to much of the functionality available through the Azure portal

Request API permissions

< All APIs

Microsoft Graph <https://graph.microsoft.com/> Docs [↗](#)

What type of permissions does your application require?

Delegated permissions

Your application needs to access the API as the signed-in user.

Application permissions

Your application runs as a background service or daemon without a signed-in user.

Request API permissions

< All APIs



Microsoft Graph

<https://graph.microsoft.com/> Docs

What type of permissions does your application require?

Delegated permissions

Your application needs to access the API as the signed-in user.

Application permissions

Your application runs as a background service or daemon without a signed-in user.

Select permissions

[expand all](#)

<input type="text" value="Calendars."/>	<input type="button" value="x"/>
Permission	Admin consent required

Calendars (1)

<input checked="" type="checkbox"/>	Calendars.Read ⓘ Read calendars in all mailboxes	Yes
<input type="checkbox"/>	Calendars.ReadWrite ⓘ Read and write calendars in all mailboxes	Yes

Add permissions

Discard

Folgende Permissions werden benötigt: Calendars.Read, Place.Read.All, User.Read.All

Request API permissions

< All APIs

<https://graph.microsoft.com/> [Docs](#)

What type of permissions does your application require?

Delegated permissions

Your application needs to access the API as the signed-in user.

Application permissions

Your application runs as a background service or daemon without a signed-in user.

Select permissions

[expand all](#)

Permission	Admin consent required
> IdentityRiskyUser	
> TeamsAppInstallation	
> TeamsTab	
▼ User (1)	
<input type="checkbox"/> User.Export.All ^① Export user's data	Yes
<input type="checkbox"/> User.Invite.All ^① Invite guest users to the organization	Yes
<input type="checkbox"/> User.ManageIdentities.All ^① Manage all users' identities	Yes
<input checked="" type="checkbox"/> User.Read.All ^① Read all users' full profiles	Yes
<input type="checkbox"/> User.ReadWrite.All ^① Read and write all users' full profiles	Yes

Add permissions

Discard

Do you want to grant consent for the requested permissions for all accounts in Umdasch Digital Retail GmbH? This will update any existing admin consent records this application already has to match what is listed below.

Yes No

^① The "Admin consent required" column shows the default value for an organization. However, user consent can be customized per permission, user, or app. This column may not reflect the value in your organization, or in organizations where this app will be used.

Configured permissions

Applications are authorized to call APIs when they are granted permissions by users/admins as part of the consent process. The list of configured permissions should include all the permissions the application needs. [Learn more about permissions and consent](#)

+ Add a permission Grant admin consent for Umdasch Digital Retail GmbH ^①

API / Permissions name	Type	Description	Admin consent req...	Status
Microsoft Graph API				...

3. Client Secret erstellen

ESignageDataConnector | Certificates & secrets

Search (Ctrl+/) < Got feedback?

Overview
Quickstart
Integration assistant

Manage

- Branding
- Authentication
- Certificates & secrets**
- Token configuration
- API permissions
- Expose an API
- App roles
- Owners
- Roles and administrators | Preview
- Manifest

Credentials enable confidential applications to identify themselves to the authentication service when receiving tokens at a web addressable location (using an HTTPS scheme). For a higher level of assurance, we recommend using a certificate (instead of a client secret) as a credential.

Certificates

Certificates can be used as secrets to prove the application's identity when requesting a token. Also can be referred to as public keys.

Upload certificate

Thumbprint	Start date	Expires	ID
No certificates have been added for this application.			

Client secrets

A secret string that the application uses to prove its identity when requesting a token. Also can be referred to as application password.

+ New client secret

Description	Expires	Value	ID
-------------	---------	-------	----

Add a client secret

Description:

Expires:

4. Werte in ESignage Data Connector eintragen

ESignageDataConnector | Certificates & secrets

Search (Ctrl+F) Got feedback?

Overview
Quickstart
Integration assistant

Manage
Branding
Authentication
Certificates & secrets
Token configuration
API permissions
Expose an API
App roles
Owners
Roles and administrators | Preview
Manifest

Support + Troubleshooting
Troubleshooting
New support request

Certificates
Certificates can be used as secrets to prove the application's identity when requesting a token. Also can be referred to as public keys.


Upload certificate

Thumbprint	Start date	Expires	ID
No certificates have been added for this application.			

Client secrets
A secret string that the application uses to prove its identity when requesting a token. Also can be referred to as application password.

+ New client secret

Description	Expires	Value	ID
My Client Secret 1	4/24/2023	[Redacted]	114410986072446c9d4c-ba3fbc41ba9



ESignage Data Connector v4.1.0

PROISING DEUTSCHLAND

Room Signage and Display Solutions

Verbindung Allgemein Monitoring

Verbindungsart: Office365 (Graph API)

Authority Host: https://login.microsoftonline.com

Client ID: ###

Client Secret: ###

Tenant: ###

Rooms: meetingroom1@umdaschdigitalretail.onmicrosoft.com

Verbindung testen

Abbrechen Speichern und Schließen

ESignageDataConnector

Search (Ctrl+F) Delete Endpoints Preview features

Overview
Quickstart
Integration assistant

Manage
Branding
Authentication
Certificates & secrets
Token configuration
API permissions
Expose an API
App roles
Owners
Roles and administrators | Preview
Manifest

Essentials

Display name: ESignageDataConnector


Application (client) ID: [Redacted]

Directory (tenant) ID: [Redacted]

Object ID: [Redacted]

Starting June 30th, 2020 we will no longer add any new features to Azure Active Directory Authentication Library (ADAL) and be upgraded to Microsoft Authentication Library (MSAL) and Microsoft Graph. [Learn more](#)

Get Started Documentation



ESignage Data Connector v4.1.0

PROISING DEUTSCHLAND

Room Signage and Display Solutions

Verbindung Allgemein Monitoring

Verbindungsart: Office365 (Graph API)

Authority Host: https://login.microsoftonline.com

Client ID: [Redacted]

Client Secret: [Redacted]

Tenant: [Redacted]

Rooms: meetingroom1@umdaschdigitalretail.onmicrosoft.com

Verbindung testen

Abbrechen Speichern und Schließen

Build your application

The Microsoft identity platform is an authentication service, open-source libraries, and application management tools. You can create modern, standards-based authentication solutions, access and protect APIs, and add sign-in for your users and customers. [Learn more](#)