



# Choose Your Camera Vaddio® Makes It Easy

#### Consider the Room Environment

- How large is the room? Where will you place the camera(s) to have an unobstructed view? Large auditoriums need higher magnification than classrooms or conference rooms. Small rooms may need a wide angle of view.
- How much light is in the room? Will the lighting be sufficient for the camera? Normal office lighting is 320 to 500 lux, while moonlight is 1 lux.

## Consider Subject Matter & Zoom

What is your subject matter? One person - head and shoulders view? Three people? A group of 20 people? How will you frame the subject matter? Will you need a zoom lens? For details, see Camera Distance & Angles of View on back.

### Consider Video Output Connections

- Vaddio cameras connect to other equipment, so consider what kind of connections you'll need. What is your camera connected to? What video output format is required?
- Will you need camera cable extensions? Vaddio's extension systems include OneLINK digital extenders and Quick Connect HSDS (High speed differential signaling) extenders which extend video, power and control. For details, see Cables and Connections on back.















#### Consider Vaddio Cameras

- For best image quality, choose RoboSHOT® 20 UHD
- For best low light performance, choose RoboSHOT 30 HDBT™
- For widest field of view/PTZ (74°), choose RoboSHOT 12, ConferenceSHOT™ 10
- For widest field of view/fixed (82°), choose WideSHOT™
- IP streaming capable: RoboSHOT 12 USB/HD-SDI/HDBT Series

RoboSHOT 30 HD-SDI/HDBT Series

RoboSHOT 20 UHD ConferenceSHOT Series

All Vaddio cameras include: IR remote, wall mount, mounting hardware, power supply, AC cord set, and EZCamera Control Adapter RJ-45F to DE-9F.

			Direct Output Pan Tilt Zoom (PTZ) Cameras							Cameras with Extension Systems						
	Consider the	UHD Cameras	HD-SDI	Cameras	HDMI C	Cameras	HDBT P	TZ Cameras	USB PTZ (	Cameras	RoboSHOT Or	eLINK Systems	Cat-5 PTZ	Z Cameras	Cat-5 Fixe	ed Cameras
У	owing to help you choose our Camera.	99								SE					9	
	Model	RoboSHOT 20 UHD	RoboSHOT 30 HD-SDI	RoboSHOT 12 HD-SDI	RoboSHOT 30 HDMI	RoboSHOT 12 HDMI	RoboSHOT 30 HDBT	RoboSHOT 12 HDBT	RoboSHOT 12 USB	ConferenceSHOT 10	RoboSHOT 30 OneLINK HDMI	RoboSHOT 12 OneLINK HDMI	RoboSHOT 30 Q-Series (Quick-Connects)	RoboSHOT 12 Q-Series (Quick-Connects)	ZoomSHOT 20	WideSHOT
	Colors	Black/Silver or White	Black or White	Black/Silver	Black or White	Black/Silver	Black or White	Black/Silver	Black/Silver	Black/Silver or White	Black or White	Black/Silver	Black or White	Black/Silver	Black/Silver	Black/Silver
ents	Room Size	Medium to large rooms	Medium to large rooms	Small to medium conference rooms, training rooms or classrooms that require a wide angle of view	Medium to large rooms	Small to medium conference rooms, training rooms or classrooms that require a wide angle of view	Medium to large rooms	Small to medium conference rooms, training rooms or classrooms that require a wide angle of view	Small to medium conference rooms, training rooms or classrooms that require a wide angle of view	Small to medium conference rooms, training rooms, classrooms	Medium to large rooms	Small to medium conference rooms, training rooms or classrooms that require a wide angle of view	Medium to large rooms	Small to medium conference rooms, training rooms or classrooms that require a wide angle of view	Medium to large rooms	Small huddle rooms that require high def video and a very wide angle of view
Room Environments	Optical Zoom	12x with 1.67 CVZ for 20x total useable	30x Optical Zoom	12x Optical Zoom (Super-Wide Mode)	30x Optical Zoom	12x Optical Zoom (Super-Wide Mode)	30x Optical Zoom	12x Optical Zoom (Super-Wide Mode)	12x Optical Zoom (Super-Wide Mode)	11X Optical Zoom (Super-Wide Mode)	30x Optical Zoom	12x Optical Zoom (Super-Wide Mode)	30x Optical Zoom	12x Optical Zoom (Super-Wide Mode)	20x Optical Zoom	3X Manual Varifocal Optical Zoom
toom Er	Horiz. Angle of View	74.0° Wide End to 3.7° Tele End	65.0° Wide End to 2.3° Tele End	73.0° Wide End to 6.6° Tele End	65.0° Wide End to 2.3° Tele End	73.0° Wide End to 6.6° Tele End	65.0° Wide End to 2.3° Tele End	73.0° Wide End to 6.6° Tele End	73.0° Wide End to 6.6° Tele End	74.0° Wide End to 7.6°Tele End	65.0° Wide End to 2.3° Tele End	73.0° Wide End to 6.6° Tele End	65.0° Wide End to 2.3° Tele End	73.0° Wide End to 6.6° Tele End	63.0° Wide End to 3.1° Tele End	82° Wide End to 27.4° Tele End, and 94.3° Diagonal
Œ	Minimum Illumination	0.75 Lux (F1.8, 50IRE, 1/30 sec (High sensitivity mode on)	1.4 Lux (F1.6, 50IRE, 1/30 sec)	1.0 Lux (F1.8, 50IRE, 1/30 sec)	1.4 Lux (F1.6, 50IRE, 1/30 sec)	1.0 Lux (F1.8, 50IRE, 1/30 sec)	0.1 Lux (F1.6, 50IRE, 1/30 sec,)	1.0 Lux (F1.8, 50IRE, 1/30 sec)	1.0 Lux (F1.8, 50IRE, 1/30 sec)	1.0 Lux (F1.8, 50IRE, 1/30 sec)	0.1 Lux (F1.6, 50IRE, 1/30 sec, color)	1.0 Lux (F1.8, 50IRE, 1/30 sec)	1.4 Lux (F1.6, 50IRE, 1/30 sec)	1.0 Lux (F1.8, 50IRE, 1/30 sec)	0.3 Lux (F1.6, 1/30 sec, 50 IRE)	0.1 Lux (1/30 Shutter Speed)
suo	Video Outputs	Simultaneous -3Gb/s HD-SDI -HDMI -IP Streaming -HDBT	Simultaneous, -3Gb/s HD-SDI -HDMI -IP Streaming	Simultaneous, -3Gb/s HD-SDI -HDMI -IP Streaming	HDMI	HDMI	Simultaneous -HDMI -HDBT -IP Streaming	Simultaneous -HDMI -HDBT -IP Streaming	Simultaneous -USB 3.0 -HDMI -IP Streaming	Simultaneous -USB 3.0 -IP Streaming	Simultaneous -HDMI -HDBT -IP Streaming	Simultaneous -HDMI -HDBT -IP Streaming	Depends on choice of Quick-Connect	Depends on choice of Quick-Connect	Depends on choice of Quick-Connect	Depends on choice of Quick-Connect
Connections	Quick-Connect Compatibility	No	No	No	No	No	No	No	No	No	No	No	Yes	Yes	Yes	Yes
ပိ	OneLINK Compatibility	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No	No	No	No
	PoE Compatibility	PoE++	PoE+	PoE+			PoE+	PoE+	PoE+	PoE+	PoE+	PoE+				
	Image Sensor	1/2.3 - Type Exmor-R, Backside illuminated image sensor	1/2.8 - Type Exmor CMOS	1/2.8 - Type Exmor CMOS	1/2.8 - Type Exmor CMOS	1/2.8 - Type Exmor CMOS	1/2.8 - Type Exmor-R Backside illuminated image sensor	1/2.8 - Type Exmor CMOS	1/2.8 - Type Exmor CMOS	1/2.8 - Type Exmor CMOS	1/2.8 - Type Exmor-R Backside illuminated image sensor	1/2.8 - Type Exmor CMOS	1/2.8 - Type Exmor CMOS	1/2.8 - Type Exmor CMOS	1/2.8 - Type Exmor CMOS	1/3 - Type Exmor CMOS
	Pixels	8.93 Megapixel (9.03 Total Megapixel)	2.14 Megapixel (2.38 Total Megapixel)	2.14 Megapixel (2.38 Total Megapixel)	2.14 Megapixel (2.38 Total Megapixel)	2.14 Megapixel (2.38 Total Megapixel)	2.14 Megapixel (2.38 Total Megapixel)	2.14 Megapixel (2.38 Total Megapixel)	2.14 Megapixel (2.38 Total Megapixel)	2.14 Megapixel	2.14 Megapixel (2.38 Total Megapixel)	2.14 Megapixel (2.38 Total Megapixel)	2.14 Megapixel (2.38 Total Megapixel)	2.14 Megapixel (2.38 Total Megapixel)	2.14 Megapixel (2.38 Total Megapixel)	1.3 Megapixel
ions	Top Resolution	UHD - 2160p/29.97	HD - 1080p/60	HD - 1080p/60	HD - 1080p/60	HD - 1080p/60	HD - 1080p/60	HD - 1080p/60	HD - 1080p/60	HD - 1080p/60	HD - 1080p/60	HD - 1080p/60	HD - 1080p/60	1080p/60	1080p/60	720p Native, 1080p Scaled
& Specifications	PTZ Motors	Silent BLDC Direct Drive Motors	Silent BLDC Direct Drive Motors	Silent BLDC Direct Drive Motor	Silent BLDC Direct Drive Motor	Silent BLDC Direct Drive Motors	Silent BLDC Direct Drive Motors	Silent BLDC Direct Drive Motors	Silent BLDC Direct Drive Motors	Stepper Motors	Silent BLDC Direct Drive Motors	Silent BLDC Direct Drive Motors	Silent BLDC Direct Drive Motors	Silent BLDC Direct Drive Motors	No Motors - Manual	No Motors - Manual
Spe	Tri-Sync Motion	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes	No	No
	Pan/Tilt Range	Pan: ±160°, Tilt: +90° to -30°	Pan: ±160°, Tilt: +90° to -30°	Pan: ±160°, Tilt: +90° to -30°	Pan: ±160°, Tilt: +90° to -30°	Pan: ±160°, Tilt: +90° to -30°	Pan: ±160°, Tilt: +90° to -30°	Pan: ±160°, Tilt: +90° to -30°	Pan: ±160°, Tilt: +90° to -30°	Pan: ±160°, Tilt: +90° to -30°	Pan: ±170°, Tilt: +90° to -30°	Pan: ±160°, Tilt: +90° to -30°	Pan: ±160°, Tilt: +90° to -30°	Pan: ±160°, Tilt: +90° to -30°	Fixed: Pan(Manual): ± 180° Tilt(Manual): ± 30°	Fixed: Pan(Manual): ± 180° Tilt(Manual): ± 30°
nal Fe	Web Server for Remote Control	Built-in	Built-in	Built-in	Built-in	Built-in	Built-in	Built-in	Built-in	Built-in	Built-in	Built-in	Built-in	Built-in		
Additional Features	Control Methods	Web Server via Browser, Telnet, RS-232 and IR Remote	Web Server via Browser, Telnet, RS-232 and IR Remote	Web Server via Browser, Telnet, RS-232 and IR Remote	Web Server via Browser, Telnet, RS-232 and IR Remote	Web Server via Browser, Telnet, RS-232 and IR Remote	Web Server via Browser, Telnet, RS-232 and IR Remote	Web Server via Browser, Telnet, RS- 232 and IR Remote	Web Server via Browser, Telnet, RS- 232 and IR Remote	Web Server via Browser, Telnet, RS-232 and IR Remote	Web Server via Browser, Telnet, RS-232 and IR Remote	Web Server via Browser, Telnet, RS-232 and IR Remote	Web Server via Browser, Telnet, RS-232 and IR Remote	Web Server via Browser, Telnet, RS-232 and IR Remote	RS-232 and IR Remote	RS-232 and IR Remote
	Invertible	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
	Video SN Ratio	>50 dB	>50 dB	>50 dB	>50 dB	>50 dB	>50 dB	>50 dB	>50 dB	>50 dB	>50 dB	>50 dB	>50 dB	>50 dB	>50 dB	>50 dB
	Camera Origin	WN made	USA MN made	WS made	WN made	USA MN made	USA MN made	MN made	MN made	WN made	USA MN made	USA MN made	WN made	USA MN made	WN made	USA MN made

## Camera Distance & Angles of View

Room size, shot requirements and a camera's zoom capabilities are three factors that you'll need to consider when choosing a video camera. Here are three examples that explain how room size, shot requirements and zoom are tied together. NOTE: All of the viewing cones, measurements and distances were created by using the Vaddio camera distance calculator **support.vaddio.com**.


#### RoboSHOT 12

The RoboSHOT 12 is an excellent pick for a variety of room sizes. As the tables indicate at 40' (12 m), full tele, the shot is 4.6' (140 cm) Horizontal x 2.6' (86 cm) Vertical or about the size of a presenter at a lectern from the waist up. On the wide end the RoboSHOT 12 is superb wide-angle camera producing an image size of 14.8' (451 cm) wide x 8.3' (253 cm) tall, which will work in virtually every small to medium conference room.



RoboSHOT 12 Image Size (Wide End)					
Distance	Image Size H & V				
10' (3 m)	14.8' H x 8.3' V (4.5 x 2.5 m)				
20' (6 m)	29.6' H x 16.65' V (9 x 5.1 m)				
30' (9 m)	44.4' H x 25' V (13.5 x 7.6 m)				
40' (12 m)	59.2' H x 33.3' V (18 x 10.1 m)				
50' (15 m)	74' H x 41.6' V (22.5 x 12.7 m)				

RoboSHOT 12 Image Size (Tele End)					
Distance	Image Size H & V				
10' (3 m)	1.1' H x 0.65' V (33 x 19 cm)				
20' (6 m)	2.3' H x 1.3' V (70 x 39 cm)				
30' (9 m)	3.5' H x 2' V (107 x 61 cm)				
40' (12 m)	4.6' H x 2.6' V (140 x 79 cm)				
50' (15 m)	5.76' H x 3.24' V (175 x 99 cm)				




#### RoboSHOT 30


The RoboSHOT 30 is an exceptional pick for a large to medium sized room, but with 65° wide angle lens and a 2.3° telephoto lens, this camera is both powerful and versatile. At 70' (21 m) the impressive lens produces an image of only 2.9' (88 cm) wide by 1.63' (50 cm) tall, which is about the size of a head and shoulder shot. Whether it is a large House of Worship, auditorium, lecture theatre or even a medium sized conference/ training room, the RoboSHOT 30 is an ideal fit.



RoboSHOT 30 Image Size (Wide End)					
Distance	Image Size H & V				
10' (3 m)	12.74' H x 7.17' V (3.9 x 2.2 m)				
20' (6 m)	25.5' H x 14.34' V (7.8 x 4.4 m)				
30' (9 m)	38.2' H x 21.5' V (11.6 x 6.5 m)				
40' (12 m)	50.1' H x 28.7' V (15.3 x 8.7 m)				
50' (15 m)	53.7' H x 35.84' V (16.4 x 10.9 m)				

lm	Image Size (Tele End)					
Distance	Image Size H & V					
20' (6 m)	0.83' H x 0.47 V (25 x 14 cm)					
30' (9 m)	1.24' H x 0.7' V (38 x 21 cm)					
40' (12 m)	38.2' H x 21.5' V (51 x 28 cm)					
50' (15 m)	50.1' H x 28.7' V (64 x 35 cm)					
60' (21 m)	53.7' H x 35.84' V (88 x 49 cm)					






#### RoboSHOT 20 UHD

The RoboSHOT 20 UHD is a 4k (2160p/30) camera that has pristine clarity and color reproduction. When used as a 1080p/60 camera the camera is simply the best Vaddio PTZ camera available to date. The camera has a 12x optical zoom with a 1.67 ClearVIEW zoom on an 8.93 Megapixel sensor that make this camera useable up to a full 20x.

RoboSHOT 20 UHD Image Size (Wide End)					
Distance Image Size H & V					
10' (3 m)	12.74' H x 7.17' V (3.9 x 2.2 m)				
20' (6 m)	25.5' H x 14.34' V (7.8 x 4.4 m)				
30' (9 m)	38.2' H x 21.5' V (11.6 x 6.5 m)				
40' (12 m)	50.1' H x 28.7' V (15.3 x 8.7 m)				
50' (15 m)	53.7' H x 35.84' V (16.4 x 10.9 m)				

RoboSHOT 20 UHD Image Size (Tele End)						
Distance	Image Size H & V					
20' (6 m)	1.3' H x 0.73' V (40 x 22 cm)					
30' (9 m)	1.94' H x 1.1' V (59 x 34 cm)					
40' (12 m)	2.6' H x 1.45' V (79 x 44 cm)					
50' (15 m)	3.23' H x 1.82' V (98 x 55 cm)					
60' (21 m)	3.88' H x 2.18' V (118 x 66 cm)					





## **Extension Systems**

Extend your reach and simplify installation with Vaddio's cable extension systems.

Cable Extension Systems for Video, Power and Control								
Product	Outputs	Distance	# Cat-5 Cables	Transport Type				
OneLINK HDMI	HDMI, IP Streaming with capable camera	328' (100 m)	One	HDBaseT				

Cable Extension Systems for Video, Power and Control								
Product	Outputs	Distance	# Cat-5 Cables	Transport Type				
Quick-Connect QMini	USB 2.0	100' (30 m)	Two	HSDS, High Speed Differential				
Quick-Connect QDVI	DVI/HDMI and Analog YPbPr	100' (30 m)	Two	HSDS, High Speed Differential				
Quick-Connect QUSB	HDMI, YPbPr and USB 2.0, IP streaming	100' (30 m)	Two	HSDS, High Speed Differential				
Quick-Connect QCCU	HDMI, YPbPr and HD-SDI	500' (152 m)	Three	HSDS, High Speed Differential				



THE ART OF EASY | milestone.com

T 800.572.2011

131 Cheshire Lane, Suite 500, Minnetonka, MN 55305

