

# MAXHUB

## Product Spec

### 1. Product Features



### 2. Microphone

Type	6-Element Array, Omnidirectional
Voice Pickup Range	4m (Radius)
Frequency Range	150Hz ~7.5kHz

### 3. Speaker

Sound Channel	1.0
Output Power	1×5W
Maximum Sound Pressure Level	85dB SPL@0.5m, 1kHz
Distortion	≤1% @1W, 1kHz
Signal to Noise Ratio	≥75dB
Frequency Range	150Hz~16kHz

### 4. I/O ports

USB Type-C	1 (Audio IN/OUT+Charge 5V/2A)
AUX 3.5mm	1 (Audio IN/OUT)
Button	6
LED Indicator light	Power /Volume/Button

### 5. Battery

# MAXHUB

Battery capacity	7.4V/2200mAh
Battery charging	Wired: 5V/2A
Continuous working time	8h (Voice communication with the maximum volume)

## 6. Bluetooth

Version	BT4.2+EDR
Operating Frequency	2.4GHz
Operating Distance	10m

## 7. Physical Specification

Dimension (Diameter × Height)	120 × 36.5mm
Dimension (package) L × W × H	225 × 158 × 50mm
Net Weight	390g
Gross Weight	692g

## 8. Accessory

USB Type-C Cable	×1
Audio Cable	×1

## 9. Environmental Condition

Operation Temperature	0°C~40°C
Operation Humidity	10%~90%RH
Storage Temperature	-20°C~60°C
Storage Humidity	10%~90%RH
Altitude	Below 5000 meters

## 10. Statement

Size and weight vary by configuration and manufacturing process. Please refer to the actual product.

The product images are for illustrative purposes only and may slightly differ in appearance, colour, size, etc. from the actual product.

# MAXHUB

---

The description, illustrations, etc. in this document may subject to change per the latest product specification and performance.

Should the changes as mentioned above in the document become necessary, the document may be updated without written notice.

MAXHUB