

MAXHUB

UC P10



HD 1080p Pro PTZ Camera With 12x Optical Zoom

**PREMIUM PERFORMANCE
AND PROFESSIONAL QUALITY AT
THE PERFECT PRICE POINT**


The MAXHUB UC P10 camera brings effortless access to mid-to-large video conferencing. Combining exceptional 1080p image quality with premium 12x optical zoom, the P10 brings every conversation to life. This wide-angle camera with PTZ control represents a new generation of crystal-clear collaboration. HD 1080p images bring depth to remote interactions, while intelligent colour optimization ensures you never miss a crucial detail.

12x Optical Zoom & 16x Digital Zoom

12x optical zoom | 16x digital zoom



12x OPTICAL ZOOM



- Focus on the parts of your meeting that matter most to you. 12x optical zoom and 16x times digital zoom means you can bring your audience's attention to even the finest details of your presentation, without any loss of clarity. Responsive autofocus keeps images sharp and clear, even after zooming.

Wide-angle PTZ Performance for Complete Coverage

Tilt 30° Pan 170° | HFoV 72.5° | Up to 255 presets



- Make sure everyone in your meeting gets the attention they deserve. HFoV 72.5° aligned with wide-angle pan and tilt control ensures full-room visibility. You can choose from 255 presets to help you jump between whiteboards and speakers instantly. With whisper-quiet motor functionality, your P10 camera won't steal the spotlight from your conversation.

Superior HD 1080p Clarity in Any Environment

Panasonic 1/2.7" CMOS | 2D & 3D DNR | WDR



After 2D & 3D DNR

Before 2D & 3D DNR

After WDR

Before WDR

➤ Low lighting conditions aren't a problem anymore. With pioneering 2D and 3D DNR and WDR technology, the P10 can deliver crisp and clear image quality, even in difficult situations. Class-leading camera lens promise 1080p professional visuals, at any distance. Mid to large-sized meetings never looked so good.



Flexible Interoperability with Current Collaboration Tools

RS232 In & Out ①

➤ You may continue using the products you like most! The P10 is a flexible camera that can work with a host of popular in-room devices and meeting tools based on RS232 protocol communication. We prioritize interoperability so you don't have to rip and replace technology to upgrade your meeting room. Build on your current investments and bring new value to your meetings.

Plug and Play Deployment with USB Simplicity

USB 3.0*1 ②

➤ Forget complicated provisioning schedules and lengthy set-up times. The P10 simply plugs into your device with a USB cord for instant deployment. Just connect to your existing meeting room monitor or display and you're ready to launch the perfect video experience.

Specification

Camera Parameters		USB Featured			
Pixel	2.07M	Operate System	Windows 7, Windows 8, Windows 10, Mac OS X, Linux, Android		
Video System	1080P, 720P, 540P, 480P, 360P, 240P etc.	Color System / Compression	YUV 4:2:2 / H.264 / MJPEG		
Sensor	1/2.7inch, CMOS	Physical Specifications			
Scanning Mode	Progressive	Dimension LxHxD	128.5x118x156.2mm		
Lens	12x, f3.5mm~42.3mm, F1.8 ~ F2.8.	Net Weight	0.91Kg		
Digital Zoom	16x(Only YUV under IR Control)	Power			
Minimal Illumination	0.5 Lux @ (F1.8, AGC ON)	Input Voltage	DC 12V		
Shutter	1/30s~1/10000s	Current Consumption	1.0A (Max)		
White Balance	Auto, Indoor, Outdoor, One Push, Manual, VAR(2500K~8000K).	Power Consumption	12W (Max)		
Backlight Compensation	Support	Environmental Conditions			
Digital Noise Reduction	2D&3D Digital Noise Reduction.	Operation Temperature	-10°C ~ 40°C		
Video S/N	≥55dB	Storage Temperature	-40°C ~ 60°C		
Horizontal Angle of View	72.5°~ 6.9°	I/O Port			
Vertical Angle of View	44.8°~ 3.9°	USB 3.0	1	RS232 OUT	1
Horizontal Rotation Range	±170°	RS232 IN	1	DC IN	1
Vertical Rotation Range	-30°~ +30°				
Pan Speed Range	1.7°~ 100°/s				
Tilt Speed Range	0.7°~ 28°/s				
H & V Flip	Support				
Image Freeze	Support				
Number of Preset	255				
Preset Accuracy	0.1°				
Video Format	YUY2 (BULK): max to 1080P@30fps YUY2 (ISOC): max to 1080P@30fps MJPEG: max to 1080P@28fps	H.264 AVC: max to 1080P@30fps H.264 SVC: max to 1080P@15fps			