

V6 Classic Series

The Classic series is MAXHUB's most popular Interactive Flat Panel for meetings, collaboration and presentations for our corporate partners. Fulfilling the need for a device which can host remote meetings and local discussions for all sizes of organization from start-up teams to multinational companies.

MAXHUB V6 Classic Series of IFP brings together all the functions a meeting room needs, such as wireless screen sharing, whiteboarding, presenting as well as video conferencing with a high-quality camera and a wide microphone range. Every meeting room should have a MAXHUB V6 Classic series to enhance teamwork and increase organizational efficiency.




Professional 4K Display

High Color Accuracy, $\Delta E \leq 2$
Wide Color Gamut, NTSC 90%




Touch Screen

20 Touch Points,
Minimum Object Recognition - 2mm



Wireless Screen Sharing

Share your screen through MAXHUB
Share app or wireless dongle




Smart Whiteboard

OCR supported,
Multiple built-in templates



Built-in Camera

48million pixels
Offer the best view in both dark/bright
scene with WDR technology




10th Gen Intel CPU

Powerful performance, fluid experience
* With use of MAXHUB PC Module



Built-in Microphone

8 meters of voice pick-up
8 mics arrays, clear conversations



Built-in Speaker

2.1 Channel
2x 10W + 20W

| Display | | | | |
|----------------------|----------------------|----------------------|----------------------|----------------------|
| Model / Part No. | C5530 | C6530 | C7530 | C8630 |
| Diagonal Size (inch) | 55 | 65 | 75 | 86 |
| Backlight | Direct-lit LED | Direct-lit LED | Direct-lit LED | Direct-lit LED |
| Panel Technology | IPS | IPS | VA | VA |
| Aspect Ratio | 16 : 9 | 16 : 9 | 16 : 9 | 16 : 9 |
| Resolution | 3840 x 2160 | 3840 x 2160 | 3840 x 2160 | 3840 x 2160 |
| Refresh Rate | 60Hz | 60Hz | 60Hz | 60Hz |
| Response Time | 8ms | 8ms | 8.5ms | 8ms |
| Brightness (typ) | 350cd/m ² | 350cd/m ² | 350cd/m ² | 350cd/m ² |
| Contrast Ratio | 1200 : 1 | 1200 : 1 | 5000 : 1 | 4000 : 1 |
| Viewing Angle | 178°/178° | 178°/178° | 178°/178° | 178°/178° |
| Color Gamut (typ) | 90% NTSC | 90% NTSC | 90% NTSC | 90% NTSC |
| Display Orientation | Landscape | Landscape | Landscape | Landscape |
| Operating Hour | 16/7 | 16/7 | 16/7 | 16/7 |

| Dimension&Weight | | | | |
|-----------------------------|---|--|---|---|
| Product Dimensions (WxHxD) | 1263 x 776 x 88 mm 49.72 x 30.55 x 3.46 inch | 1488 x 903 x 88 mm 58.58 x 35.55 x 3.46 inch | 1709 x 1026 x 87 mm 73.35 x 44.88 x 8.86 inch | 1957.1 x 1160.1 x 100.2 mm 77.05 x 45.67 x 3.94 inch |
| Shipping Dimensions (WxHxD) | 1392 x 847 x 220mm 54.8 x 33.35 x 8.66 inch | 1638 x 1005 x 208mm 64.09 x 39.57 x 8.19 inch | 1863 x 1140 x 225 mm 73.35 x 44.88 x 8.86 inch | 2110 x 1283 x 225 mm 83.07 x 50.51 x 6.86 inch |
| Net Weight (kg /pounds) | 26.25kg / 57.87 lbs | 36.25kg / 79.92 lbs | 48.3kg / 106.48 lbs | 59.75kg / 131.73 lbs |
| Gross Weight (kg /pounds) | 34.2kg / 75.40 lbs | 46.75kg / 103.07 lbs | 62.8kg / 138.45 lbs | 77.00kg / 169.76 lbs |
| Wall Mount (VESA) | 400 x 200mm / 15.75 x 7.78inch | 600 x 400mm / 23.62 x 15.75inch | 800 x 400mm / 31.50x15.75inch | 800 x 600mm / 31.50 x 23.62inch |
| Screws For VESA | M8 x 25mm / M8 x 0.99inch | M8 x 25mm / M8 x 0.99inch | M8 x 25mm / M8 x 0.99inch | M8 x 25mm / M8 x 0.99inch |



| POWER | | | | |
|-----------------------|--------------------|--------------------|--------------------|--------------------|
| Power Supply | AC100-240V,50/60Hz | AC100-240V,50/60Hz | AC100-240V,50/60Hz | AC100-240V,50/60Hz |
| Max Power Consumption | 300W | 350W | 400W | 400W |
| Standby | ≤0.5W | ≤0.5W | ≤0.5W | ≤0.5W |

| Touch System | |
|---|--|
| Touch Sensor | IR Touch |
| Max Touch Points Supported | 20 |
| Accuracy | ±1mm |
| Object Recognition Range | ≥2mm |
| Glass | Zero parallax , 3mm Angi-glare, Antibacterial |
| Supported Operating System (Touch Return) | Windows10/Windows8/Windows7/WindowsXP/ Android/Linux/Mac OS X/Chrome OS |

| Connectivity | |
|----------------|--|
| Input | HDMI IN x 1 , USB 2.0 x 1, USB 3.0 x 2, TOUCH 2.0 x 1 , USB Type-C x 2 |
| Audio | Audio out x 1 |
| Control | RS232 x 1 |
| PC Module Slot | Yes, 3840 x 2160@60fps |
| PC Module | MAXHUB PC Module |
| Wifi Module | SI06 |

| Camera/Audio/Microphone | |
|-------------------------|--|
| Built-in Camera | Yes, Single Camera, 48MP |
| Camera Features | Auto Frame / Speaker Tracking |
| Built-in Speakers | 2.1 Channel , 2x10W+20W |
| Microphone Array | 8 x Far-field , beam-forming microphone - max 8m range |

| Environment | |
|-----------------------|-----------|
| Operating Temperature | 0℃~40℃ |
| Storage Temperature | 10%~90%RH |
| Operating Humidity | -20℃~60℃ |
| Storage Humidity | 10%~90%RH |

| What's In The Box | |
|-------------------|---|
| Standard | Power Cord, 1 x Wifi Adapter, 2 x Passive Stylus, 1 x Wall Mount, 1 x Type-C Cable (1.8m 70.9inch) |
| Optional | <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  <p>wireless dongle</p> </div> <div style="text-align: center;">  <p>ST41B</p> </div> <div style="text-align: center;">  <p>ST23C</p> </div> <div style="text-align: center;">  <p>EST09</p> </div> <div style="text-align: center;">  <p>EST11</p> </div> </div> |